



Pine Integrated LED Path Light

Color Temperature



Brightness



Light Spread



Features

- 17" brass stem and classic hat with integrated LED
- Custom engineered driver and marine grade virgin brass housing
- Clear polycarbonate lens allows for unobstructed 360° illumination
- EZClip connector allows for LED replacement in seconds
- Independent LED and driver modules for easy maintenance
- Potted driver protects from moisture and helps dissipate heat
- Modern innovative design allowing for efficient thermal dissipation

Dimensions and Images



Product Specifications

LED	Brand	CREE
	Color Temperature	2800K
	Dimmable	Yes
	CRI	80+
	Lumens	300
	Lumens per Watt	60
Optics	Light Spread	360° unobstructed illumination
	External Lens	Clear polycarbonate replaceable lens
	Internal Optic	N/A
Electrical	Working Voltage	10V-15V
	Socket	N/A
	Lead Wire	5 ft. 18 AWG SPT-1 wire with soldered shrink wrapped connection
	Working Temperature	-40°F to 219°F (-40°C to 104°C)
Housing	Material	Marine grade virgin brass
	Angle Adjustment	N/A
	Color	Sunset Bronze, powder coating available
	Ingress Protection	IP65 Dust tight and protected against projected water
	Weather Protection	Rubber base plug to keep out moisture and bugs
Dimensions	Height	Riser: 17 in. (432 mm) Hat: 2.4 in. (62 mm)
	Diameter (width)	Riser: 1.25 in. (32 mm) Hat: 7.0 in. (178 mm)
	Weight	2.3 lbs (1.1 kg)
	Mounting Options	Composite stake
	Warranty	Lifetime on brass, 5 years for LED components
	LED Life Rating	50,000 hours
	Standards	ETL and cETL (pending)